

HOT DIP GALVANIZED

ETL LISTED

Velkor Hot Dip Galvanized EMT is ETL Listed to UL 797 standard and manufactured in accordance with ANSI C80.3, providing dependable performance for commercial and industrial electrical installations.

HOT-DIP GALVANIZED COATING

Hot-dip galvanized inside and outside, delivering superior corrosion resistance for outdoor, coastal, and other demanding environments.

APPLICATIONS

Suitable for exposed or concealed installations in wet or dry locations where maximum corrosion protection is required.

QUALITY ASSURANCE

Every production batch is inspected for dimensions, zinc coating thickness, weld integrity and bend performance before shipment.

SIZE CHART

STANDARD: UL797

VELKOR CAT#	TRADE SIZE	OUTSIDE Ø (MM)	WALL (MM)	LENGTH (MM)	WEIGHT (KG)	ZINC COATIN
VK-050H	1/2"	17.9	1.07	3050	1.388	40~60
VK-075H	3/4"	23.4	1.25	3050	2.135	40~60
VK-100H	1"	29.5	1.45	3050	3.136	40~60
VK-125H	1 1/4"	38.4	1.65	3050	4.675	40~60
VK-150H	1 1/2"	44.2	1.65	3050	5.413	40~60
VK-200H	2"	55.8	1.65	3050	6.888	40~60
VK-250H	2 1/2"	73	1.83	3050	10.041	40~60
VK-300H	3"	88.9	1.83	3050	12.284	40~60
VK-350H	3 1/2"	101.6	2.11	3050	16.184	40~60
VK-400H	4"	114.3	2.11	3050	18.25	40~60

*This conduit is conforms to UL-797 standard, certified to CSA C22.2 No. 83.1 standard

**VELKOR INDUSTRIES**

Sales Office: 33 Park View Ave, Jersey City, New Jersey, United States, 07302
Factory: Puyang Industrial Zone, Xiaoshan, Hangzhou, Zhejiang, China, 311200

Website: Velkor.co
Tel: +1 (201) 204-6512
Email: Info@velkor.co
Facebook: Velkor Industries
Instagram: Velkor Industries



Website

Document No.: VK-EMT-TDS-001
Revision: A
Issue Date: August, 2026
Applicable Standard: UL797, ANSI C80.3