

LIQUID-TIGHT STRAIGHT CONNECTOR

INSULATED THROAT - ZINC DIE CAST

Description:

Designed to terminate liquid-tight flexible metallic or nonmetallic Type B conduit at a box or enclosure while maintaining a sealed straight entry

- **Material:** Zinc Die-Cast
- **Type:** Straight Compression Connector
- **Conduit:** LFMC/LFNC Type B
- **Application:** Liquid-tight conduit to box or enclosure




VELKOR TIP | Straight Sealed Entry

Fully seat the conduit before tightening the compression nut and box locknut.

Insulated throat helps protect conductors from abrasion at the fitting entry.

Compression construction supports a sealed conduit entry when installed with the specified conduit and enclosure.



VELKOR ITEM NO.	SIZE	A (in.)	B (in.)	C (in.)
471	1/2"	1.50	1.38	0.42
472	3/4"	1.60	1.72	0.42
473	1"	1.79	1.90	0.55
474	1-1/4"	1.90	2.29	0.55
475	1-1/2"	1.93	2.63	0.52
476	2"	2.08	3.15	0.585
477	2-1/2"	3.02	4.20	0.775
478	3"	3.53	4.91	0.92
480	4"	3.87	5.92	0.98

A: Max. outside diameter B: Overall length

C: Male thread length (in.)

VELKOR FLEX CONDUIT ACCESSORIES



VELKOR INDUSTRIES

Sales Office: 33 Park View Ave, Jersey City, New Jersey, United States, 07302
Factory: Puyang Industrial Zone, Xiaoshan, Hangzhou, Zhejiang, China, 311200

Website: Velkor.co
Tel: +1 (201) 204-6512
Email: Info@velkor.co
Facebook: Velkor Industries
Instagram: Velkor Industries



Website

Document No.: VK-RIGID-TDS-471
Revision: A
Issue Date: August, 2026
Applicable Standard: UL514B