

5 STARS VELKOR SIGNITURE EMT

PREMIUM ELECTRO-GALVANIZED

Our Signature EMT features a heavy electro-galvanized coating, 275 g/m² Zinc coating offers 30~40 µm thick for significantly improved corrosion resistance over standard EMT.

VALUE

Designed as an economical alternative to hot-dip galvanized conduit for most indoor and sheltered outdoor applications.

BENDING PERFORMANCE

Manufactured from premium low-carbon steel to ensure smooth bending without cracking or excessive springback.

SURFACE FINISH

Uniform zinc coating and smooth interior provide easy wire pulling and professional installation.

VELKOR CAT#	TRADE SIZE	OUTSIDE Ø (MM)	WALL (MM)	LENGTH (MM)	WEIGHT (KG)	ZINC COATING (µm)
VK-050S	1/2"	17.9	1.00	3000	1.25	30~40
VK-075S	3/4"	23.4	1.2	3000	1.97	30~40
VK-100S	1"	29.5	1.4	3000	2.91	30~40
VK-125S	1 1/4"	38.4	1.6	3000	4.36	30~40
VK-150S	1 1/2"	44.2	1.6	3000	5.04	30~40
VK-200S	2"	55.8	1.6	3000	6.42	30~40
VK-250S	2 1/2"	73	1.8	3000	9.48	30~40
VK-300S	3"	88.9	1.8	3000	11.60	30~40
VK-350S	3 1/2"	101.6	2.1	3000	15.46	30~40
VK-400S	4"	114.3	2.1	3000	17.43	30~40

*This conduit is NOT conforms to UL-797 standard, certified to CSA C22.2 No. 83.1 standard



VELKOR INDUSTRIES

Sales Office: 33 Park View Ave, Jersey City, New Jersey, United States, 07302
Factory: Puyang Industrial Zone, Xiaoshan, Hangzhou, Zhejiang, China, 311200

Website: Velkor.co
Tel: +1 (201) 204-6512
Email: Info@velkor.co
Facebook: Velkor Industries
Instagram: Velkor Industries



Website

Document No.: VK-EMT-TDS-001
Revision: A
Issue Date: August, 2026
Applicable Standard: UL797, ANSI C80.3